

GROUP 3

ABC categories · theory questions

59 questions

1. A vehicle may not be operated if:

1. The remaining tread depth of the tires of a passenger car is 1.8 mm.
2. **The hydraulic brake system is not leak-tight.**
3. In both cases.

Answer: 2

2. A vehicle may not be operated if:

1. The remaining tread depth of the tires of a truck is 1.6 mm.
2. **The pressure gauge of the pneumatic brake system does not operate.**
3. In both cases.

Answer: 2

3. A vehicle may not be operated if:

1. There is movement in steering parts or assemblies that is not provided for by the design, or threaded connections are not tightened.
2. A fire extinguisher is missing from a truck.
3. **In both cases.**

Answer: 3

4. A vehicle may not be operated if:

1. The exterior lighting devices do not operate in the prescribed mode.
2. The remaining tread depth of the tires of a motorcycle is 0.6 mm.
3. **In both cases.**

Answer: 3

5. A vehicle may not be operated if:

1. **The rear fog lights are connected to the vehicle's brake lights.**
2. The engine coolant temperature gauge does not operate.
3. In both cases.

Answer: 1

6. A vehicle may not be operated if:

1. The engine operates intermittently.
2. **The tires have localized damage exposing the tire cord.**
3. The interior lighting devices of a passenger car do not operate.
4. In all of the listed cases.

Answer: 2

7. A vehicle may not be operated if:

1. A motorcycle without a sidecar does not have an emergency warning triangle.
2. **The tires do not correspond to the vehicle model in size or permitted load capacity.**
3. In both cases.

Answer: 2

8. A vehicle may not be operated if:

1. Even one wheel-fastening bolt is missing.
2. Tires with different tread patterns are installed on the same axle.
3. **In both cases.**

Answer: 3

9. A vehicle may not be operated if:

1. The head restraints provided by the vehicle's design are missing.
2. New and retreaded tires are installed on the same axle.
3. **In both cases.**

Answer: 3

10. A vehicle may not be operated if:

1. The content of harmful substances in the exhaust gases exceeds the limits established by the legislation of the Republic of Armenia.
2. The footrests provided by the motorcycle's design are missing.
3. **In both cases.**

Answer: 3

11. A vehicle may not be operated if:

1. The engine crankcase ventilation system is not leak-tight.
2. The engine fuel system is not leak-tight.
3. **In both cases.**

Answer: 3

12. A vehicle may not be operated if:

1. The engine crankcase ventilation system is not leak-tight.
2. Winter and non-winter tires are installed on the same axle.
3. **In both cases.**

Answer: 3

13. A vehicle may not be operated if:

1. The windshield washers provided by the vehicle's design do not operate.
2. The engine's external noise level exceeds the limits established by the standard.
3. **In both cases.**

Answer: 3

14. A vehicle may not be operated if:

1. The engine operates intermittently.
2. The rear fog lights are not connected to the brake lights.
3. **The windshield washers provided by the vehicle's design do not operate.**
4. In all of the listed cases.

Answer: 3

15. A vehicle may not be operated if:

1. Items or objects that may cause injury to road users are installed on the vehicle.
2. The horn does not operate.
3. **In both cases.**

Answer: 3

16. A vehicle may not be operated if:

1. **There is excessive play in the connections between the motorcycle frame and the sidecar frame.**
2. Yellow-light fog lamps are installed at the front.
3. In both cases.

Answer: 1

17. A vehicle may not be operated if:

1. **A first-aid kit is missing from a truck.**
2. White reflectors are installed at the front.
3. In both cases.

Answer: 1

18. A vehicle may not be operated if:

1. A first-aid kit is missing from a motorcycle with a sidecar.
2. The trailer support-coupling device is defective.
3. **In both cases.**

Answer: 3

19. A vehicle may not be operated if:

1. The seat belts provided by the vehicle's design do not operate.
2. Items or objects that restrict the driver's field of vision are installed within the driver's field of view.
3. **In both cases.**

Answer: 3

20. A vehicle may not be operated if:

1. **Changes or modifications have been made to the vehicle's design without permission from the vehicle registration authority.**
2. Yellow-light turn signals are installed at the front.
3. In both cases.

Answer: 1

21. A vehicle may not be operated if:

1. A motor vehicle used for practical driving instruction does not have the required identification sign.
2. The fuel gauge does not operate.
3. In both cases.

Answer: 1

22. A motorcycle may not be operated if:

1. The safety bars provided by its design are missing.
2. The minimum remaining tire tread depth is 1.6 mm.
3. In both cases.

Answer: 1

23. A vehicle may not be operated if:

1. Yellow-light turn signals are installed at the front.
2. Even one wheel-fastening bolt is missing.
3. In both cases.

Answer: 2

24. A vehicle may not be operated if:

1. Amber-light turn signals are installed at the front.
2. The trailer towing device is defective.
3. In both cases.

Answer: 2

25. A vehicle may not be operated if:

1. White reflectors are installed at the front.
2. The trailer towing device is defective.
3. In both cases.

Answer: 2

26. A vehicle may not be operated if:

1. The seat belts provided by the vehicle's design are missing.
2. White-light backup lamps are installed at the rear.
3. In both cases.

Answer: 1

27. A motorcycle with a sidecar may not be operated if:

1. The transverse passenger handhold on the seat, as provided by the design, is missing.
2. The remaining tire tread depth is 0.6 mm.
3. A first-aid kit is missing.
4. In all of the listed cases.

Answer: 4

28. A vehicle may not be operated if:

1. The interior lighting devices of a passenger car do not operate.
2. **The head restraints provided by the vehicle's design are missing.**
3. In both cases.

Answer: 2

29. A vehicle may not be operated if:

1. Red reflectors are installed at the rear.
2. **The speedometer provided by the vehicle's design does not operate.**
3. In both cases.

Answer: 2

30. A vehicle may not be operated if:

1. The total play in the steering system of a passenger car exceeds 10 degrees.
2. The mud flaps and splash guards provided by the vehicle design are missing.
3. **In both cases.**

Answer: 3

31. A vehicle may not be operated if:

1. A first-aid kit is missing from a passenger car.
2. Red-light backup lamps are installed at the rear.
3. **In both cases.**

Answer: 3

32. A vehicle may not be operated if:

1. **The remaining tread depth of the tires on a passenger-car trailer is less than 1.6 mm.**
2. Amber-light turn signals are installed at the rear.
3. In both cases.

Answer: 1

33. A vehicle may not be operated if:

1. The hydraulic brake system is not leak-tight.
2. White-light turn signals are installed at the rear.
3. **In both cases.**

Answer: 3

34. A vehicle may not be operated if:

1. Tires of different constructions are installed on the same axle.
2. The engine fuel system is not leak-tight.
3. **In both cases.**

Answer: 3

35. A vehicle may not be operated if:

1. **The horn does not operate.**
2. The cooling system does not maintain a stable operating temperature for the engine.
3. In both cases.

Answer: 1

36. A vehicle may not be operated if:

1. **There is movement in steering parts or assemblies that is not provided for by the design.**
2. White-light turn signals are installed at the front.
3. In both cases.

Answer: 1

37. A vehicle may not be operated if:

1. The engine operates intermittently.
2. **The tires have localized damage exposing the tire cord.**
3. In both cases.

Answer: 2

38. A passenger-car may not be operated if:

1. **A first-aid kit is missing.**
2. The remaining tire tread depth is 2.2 mm.
3. In both cases.

Answer: 1

39. A vehicle may not be operated if:

1. For a bus built on a passenger-car chassis, the total play in the steering system exceeds 10 degrees.
2. The mudguards and splash guards provided by the vehicle's design are missing.
3. **In both cases.**

Answer: 3

40. A vehicle may not be operated if:

1. The cargo-bed door latch provided by the vehicle's design does not operate.
2. The cab door latch provided by the vehicle's design does not operate.
3. **In both cases.**

Answer: 3

41. A vehicle may not be operated if:

1. Red-light turn signals are installed at the rear.
2. **The rear protective device provided by the vehicle's design is missing.**
3. In both cases.

Answer: 2

42. A vehicle may not be operated if:

1. The power steering system provided by the vehicle's design is defective or missing.
2. The horn does not operate.
3. In both cases.

Answer: 1

43. A vehicle may not be operated if:

1. The parking brake system does not hold the vehicle stationary on the gradient specified by the standard.
2. The leak-tightness of the transmission seals is compromised.
3. In both cases.

Answer: 3

44. A vehicle may not be operated if:

1. The spare-wheel holder does not operate.
2. The leak-tightness of the rear-axle seals is compromised.
3. In both cases.

Answer: 3

45. A vehicle may not be operated if:

1. There are visible tears in the webbing of the seat belts provided by the vehicle's design.
2. The vehicle is not equipped with fog lamps.
3. In both cases.

Answer: 1

46. A vehicle may not be operated if:

1. The engine-hood latch provided by the vehicle's design does not operate.
2. The rear side windows are curtained and two side rear-view mirrors are installed.
3. In both cases.

Answer: 1

47. A vehicle may not be operated if:

1. The rear side windows are curtained and two side rear-view mirrors are missing.
2. The window heating and defogging devices provided by the vehicle's design do not operate.
3. In both cases.

Answer: 3

48. A vehicle may not be operated if:

1. The fuel-tank cap provided by the vehicle's design does not operate.
2. The front side windows are curtained.
3. In both cases.

Answer: 3

49. A vehicle may not be operated if:

1. The horn does not operate.
2. The windows provided by the vehicle's design are missing.
3. **In both cases.**

Answer: 3

50. A vehicle may not be operated if:

1. There are cracks in a wheel rim or wheel disc.
2. There are visible distortions in the shape or dimensions of the wheel-rim mounting holes.
3. **In both cases.**

Answer: 3

51. A vehicle may not be operated if:

1. **The exterior lighting devices and reflectors are dirty.**
2. The front and rear protective devices are dirty.
3. In both cases.

Answer: 1

52. A vehicle may not be operated if:

1. Lamps or lenses are missing from the lighting devices.
2. Lenses or lamps that do not correspond to the type of the lighting device are used.
3. **In both cases.**

Answer: 3

53. A vehicle may not be operated if:

1. **The exterior lighting devices and reflectors are dirty.**
2. Exterior lighting devices from a different make of vehicle are installed on a discontinued vehicle.
3. In both cases.

Answer: 1

54. A vehicle may not be operated if:

1. **Tires with different tread patterns are installed on the same axle.**
2. The remaining tire tread depth of a passenger car is 1.6 mm.
3. In both cases.

Answer: 1

55. A vehicle may not be operated if:

1. The remaining tire tread depth of a truck is 1.4 mm.
2. **Yellow reflectors are installed at the front.**
3. In both cases.

Answer: 2

56. A vehicle may not be operated if:

1. Yellow reflectors are installed at the rear.
2. Yellow reflectors are installed at the front.
3. **In both cases.**

Answer: 3

57. A vehicle may not be operated if:

1. An "Oversized Cargo" identification sign with white and red reflective stripes is installed at the rear.
2. The remaining tire tread depth of a moped is 0.7 mm.
3. **In both cases.**

Answer: 3

58. A vehicle may not be operated if:

1. The "Doctor" identification sign is missing from an automobile driven by a physician-driver.
2. **The fuel-tank cap provided by the vehicle's design does not operate.**
3. In both cases.

Answer: 2

59. A vehicle may not be operated if:

1. **Tires with different tread patterns are installed on the same axle.**
2. A "Transportation of Children" identification sign with a yellow reflective background and red reflective border is installed at the front.
3. In both cases.

Answer: 1